

5 **FLEXURAL PIVOT FOR ROTARY DISC DRIVE ACTUATOR**

Related Applications

 This application claims the benefit of United States Provisional
10 Application Number 60/229,569, filed August 30, 2000, and United States
 Provisional Application Number 60/250,647, filed December 1, 2000.

Field of the Invention

15 The present invention relates generally to disc drives. More
 particularly, the present invention relates to pivots for use with disc drive
 actuators.

Background of the Invention

20 A typical magnetic disc drive includes one or more read/write heads
 for reading data from or writing data to one or more discs mounted on a
 spindle motor. The data is stored in generally concentric tracks on the disc
 surfaces. During drive operations, the read/write heads are positioned at
25 selected radial locations while the discs are rotated by the spindle motor.
 Rotary actuators are often employed to carry the read/write heads to the
 desired locations. The actuator is coupled to a voice coil motor which
 provides the torque for rotating the actuator about its pivot. Ball bearing
 pivots are typically chosen for their compactness. However, ball bearings
30 operate with some degree of pre-load and friction, which can lead to non-
 linearity in the movement of the actuator.

09894430 "062701
107290" 0844860

5 Flexural pivots appear to offer a feasible alternative to ball bearing
pivots in that there is no stiction and that the resolution of positioning can be
essentially a function of the servo control system. Attempts have been made
in the past to incorporate flexural pivots into disc drives, such as the pivot
systems described in the United States patent number 5,504,641, issued to Diel
10 on April 2, 1996, and the United States patent number 5,029,030, issued to
Luecke on July 2, 1991. However, these designs include large, unwieldy
springs which are unsuitable in modern disc drives where size is an important
consideration.

 General purpose flexural pivots have also been designed, such as those
15 of the type described in United States patent number 3,811,665, issued to
Seelig on May 21, 1974. In such flexural pivots, two flat springs are assembled
so that a solid center of one spring is disposed within an open center of the
other spring. The springs are coupled at their longitudinal edges to undercut
slots inside a circular sleeve. Such flexural pivots can be difficult to assemble,
20 however, and no pivots of this type have been successfully incorporated into
disc drives. There remains therefore a need for an improved flexural pivot for
use with a rotary actuator, one which eliminates the problems associated with
conventional ball bearing cartridges while being suitable for use in modern
disc drives.

034430-062701

5

Summary of the Invention

The present invention relates to flexural pivots for use with rotary disc drive actuators. According to a preferred embodiment, the pivot can be substantially disposed in a cavity of the actuator. The pivot includes a first
10 member that is coupled to the cavity wall and a second member that is mounted to a disc drive housing component of the disc drive. At least two leaves join the first member to the second member. Each of the leaves extend from at least one external surface of the member. The leaves are transversely disposed relative to one another.

15 In one embodiment, the cavity is configured with two end walls that define a recess in slidable engagement with the second member. The two end walls serve to limit the rotation of the actuator by coming into abutment with the second member. In another embodiment, the cavity further includes a first recess shaped to locate the first member. Preferably, two washers are secured
20 to each leaf such that the two washers are spaced apart by a same distance for all the leaves. According to a preferred embodiment, the center of rotation of the pivot is generally coincidental with the center of mass of the actuator.

These and various other features as well as advantages which characterize the present invention will be apparent upon reading of the
25 following detailed description and review of the associated drawings.

Brief Description of the Drawings

FIG. 1 is a perspective view of a disc drive in which one embodiment of
30 the present invention is implemented.

5 FIG. 2 is a perspective view of an actuator according to a preferred embodiment of the present invention.

 FIG. 3 is a perspective view of the flexural pivot of FIG. 2.

 FIG. 4 is a perspective view of an alternative embodiment of the flexural pivot.

10 FIG. 5 shows the flexural pivot of FIG. 4 incorporating the use of washers.

 FIG. 6 is a perspective view of an embodiment having two leaves.

 FIG. 7 is a perspective view of an alternative embodiment with endplates.

15 FIG. 8 shows the flexural pivot of FIG. 7 in assembly with clamps.

 FIG. 9 illustrates alternative shapes for the first member and second member of a flexural pivot according to the present invention.

 FIG. 10 is a perspective view of a flexural pivot according to an alternative embodiment of the present invention.

20

Detailed Description

Referring now to FIG. 1, there is illustrated a disc drive (10) with a number of discs (12) secured to a spindle (14) by a disc clamp (16). The discs
25 (12) are formatted for storing data in circular tracks. Read/write heads (18), supported at the tip of each actuator arm (20), are provided to read and record data to the discs (12). The actuator arms (20) extend transversely from an actuator body (22) of an actuator (24) that is configured for rotational movement about an axis (26) such that the read/write heads (18) can be
30 positioned at the desired radial location and can thus read/write to the selected track.

FIG. 10 is a perspective view of a flexural pivot according to an alternative embodiment of the present invention.

5 The actuator (24) is coupled to a voice coil motor (28) which includes a magnet (30) secured to a disc drive housing. The housing of the disc drive shown in FIG. 1 has a base (32) and a cover (34) which when in assembly with a gasket (36) provide a sealed environment for the various disc drive components mounted therein. The present invention, however, is not limited
10 to disc drives of such configurations and can be applied to disc drives with other housing structures.

 From the actuator body (22), support arms (38) extend to hold a coil (40) adjacent to the magnet (30). The support arms (38) are disposed diametrically opposite the actuator arms (20), to provide a center of mass at
15 the actuator body. When the coil (40) is energized, resultant torque acting on the actuator causes the actuator (24) to rotate relative to the base (32) of the disc drive. Disc drive control circuitry, most of which is embodied in a printed circuit board assembly (42) mounted to the base (32), controls the current provided to the coil (40), and thus controls the direction and degree of rotation
20 of the actuator (24).

 The actuator body (22) is provided with a cavity (44) extending along the axis of rotation (26). According to an embodiment of the present invention, there is provided a flexural pivot (46) inside the cavity (44) to enable rotation of the actuator (24) in a transverse plane, as is illustrated in
25 FIG. 2. A preferred embodiment of the pivot (46) is shown in greater detail in FIG. 3. The pivot (46) includes a first member (48) with two external inclined surfaces (50) inclined towards a virtual center of rotation of the pivot. The inclined surfaces (50) are separated by a third surface (54) that is configured to abut the wall (56) defining the cavity (44). The first member (48) is secured to
30 the actuator body (22) by a transversely located set screw threadably engaged to the actuator body (22) and the first member (48).

0929430-062701

5 The pivot (46) further includes a second member (58) also having two
external inclined surfaces (60) inclined towards the center of rotation of the
pivot. These inclined surfaces (60) need not have the same angle of separation
as the inclined surfaces (50) of the first member. The second member (58) is
configured with mounting features (62) for mounting to the base (32) or to the
10 cover (34) of the disc drive. For example, the second member (58) can be
secured by the use of a set screw that engages an axial tapped hole (63) in the
second member and a similarly tapped hole in the base (32) or the cover (34)
of the disc drive. Alternatively, the second member (58) can also be secured to
both the base (32) and the cover (34) of the disc drive.

15 The pivot (46) includes a plurality of leaves (64) joining the first
member (48) and the second member (58). Each leaf (64) begins from one of
the inclined surfaces (50) of the first member, traversing the center of rotation,
and ending at one of the inclined surfaces (60) of the second member.
Adjacent leaves begin from alternate inclined surfaces of the first member to
20 end at alternate inclined surfaces of the second member. The center of
rotation of the pivot is generally at the point where the leaves (64) intersect,
which is preferably designed to be near to, or to coincide with, the center of
mass of the actuator. The angle of separation 65 of the adjacent leaves, in the
relaxed state of the pivot, may be varied in different embodiments to obtain a
25 different torsional stiffness.

 According to one embodiment of the present invention, the pivot (46) is
formed as a monolithic unit by electrical discharge machining of a solid piece
of metal.

 According to another embodiment as shown in FIG. 4, the leaves (64)
30 are separate thin flat strips of steel which are coupled by fasteners (66) to the
first member (48) and second member (58) at their respective ends (68, 69).

FD-2290-08446860

5 Fasteners such as screws can be used. Preferably, rectangular washers (70) are inserted between the leaves (64) and the fasteners (66) so that the flexure lengths of the leaves are more or less the same, being kept to the distance between the edges (71, 72) of the respective inclined surfaces (50, 60). One example of this is illustrated in FIG. 5.

10 Referring to FIG. 6 for an alternative embodiment, the leaves 64 may include a flange (73) at both ends (68, 69) for attachment to the whole length of the respective inclined surface (50, 60).

In yet another embodiment which is shown in FIG. 7, the pivot (46) includes endplates (74) transversely disposed at both ends of the second
15 member (58). The endplates (74) allow for abutment against the base (32) and the cover (34) of the disc drive and can thus be adapted for mounting to the disc drive housing components by fasteners or adhesives. Clearance is provided between the endplates and the ends (75) of the first member so as not to hinder the movement of the first member. Clamps (76) can be added, if
20 so desired, to facilitate mounting to the respective disc drive housing component (32, 34). In the example shown in FIG. 8, a screw (78) is used to close the gap (80) between the ends of the clamp, and thereby secures the clamp to the endplates.

Referring back to FIG. 2, the cavity preferably includes a first recess (82)
25 for locating the first member (48). A second recess (84) may also be provided such that end walls (86) of the second recess act as limit stops when the second member (58) comes into abutment with the respective end walls (86) in the course of its rotation.

The first member 48 and the second member 58 need not have arcuate
30 cross-sections to complement the shape of the cavity 44. Different shapes may

09894430 062701

5 be chosen, and possible alternative shapes are illustrated in FIG. 9 for exemplary purposes only.

Referring to FIG. 10, another embodiment of the present invention is shown. A pivot (46) of this embodiment can be easily fitted within the cavity (44) of the actuator (24) with the first member (48) attached to the wall (56) of
10 the cavity. The second member (58) can be similarly provided with features (not shown) for mounting to the housing component (such as 32). Two leaves (64) extending from the second member (58) are attached to external surfaces (50) of the first member. When the pivot (46) is in its relaxed state, as shown, the two leaves (64) are at an angle (65) to one another. Otherwise, the leaves
15 (64) bend so that the first member is rotated relative to a center of rotation represented by an axis (26).

Disclosed is a flexural pivot that can be easily incorporated with rotary actuators traditionally designed for use with a ball bearing pivot cartridge. In addition, it avoids the difficulties encountered by conventional designs when
20 trying to assemble intersecting flat springs within a cylindrical sleeve. Furthermore, in comparison with conventional flexural pivots that are located outside the actuator body, the present invention provides a compact pivot that can be mounted substantially in a cavity of the actuator body such that the center of rotation of the actuator is located nearer the center of mass.

25 Alternatively, embodiments of the present invention may be described as follows:

In a first contemplated embodiment, a pivot (such as 46) can be substantially disposed in a cavity (44) that is defined by a wall (56) of an actuator (24). The pivot (46) includes a first member (48) that is coupled to the
30 wall (56) and a second member (58) that has mounting features (such as 62, 63) for mounting to a disc drive housing component (such as 32, 34) of the disc

107290-034550

5 drive (10). The first member (48) has at least one first external surface (50).
The pivot includes at least two leaves (64) transversely disposed at an angle
(65) to one another, where each of the leaf (64) joins one of the first external
surfaces (50) to the second member (58) such that the actuator (24) is pivotable
with respect to the disc drive housing component (such as 32, 34) about an
10 axis (26).

In another contemplated embodiment, the cavity (44) is configured
with two end walls (86) that define a recess (84) in slidable engagement with
the second member (58). The two end walls (86) serve to limit the rotation of
the actuator (24) by coming into abutment with the second member (58). In
15 another embodiment, the cavity (44) further includes a first recess (82) shaped
to locate the first member (48). Preferably, two washers (70) are secured to
each leaf (64) such that the two washers (70) are spaced apart by a same
distance for all the leaves (64). According to a preferred embodiment, the
center of rotation of the pivot (46) is generally coincidental with the center of
20 mass of the actuator (24). Preferably, each of the first external surfaces (50) is
inclined towards the center of rotation. In an alternative embodiment, the
second member (58) may include second mounting features (62) for mounting
to a second disc drive housing component (such as 32, 34).

It is to be understood that even though numerous characteristics and
25 advantages of various embodiments of the present invention have been set
forth in the foregoing description, together with details of the structure and
function of various embodiments of the invention, this disclosure is
illustrative only, and changes may be made in detail, especially in matters of
structure and arrangement of parts without departing from the scope and
30 spirit of the present invention.

1.0 2290 08445850